Modello	TK 150	TK 500 /TK500H	TK1000/TK1000H	TK2000/TK2000H	TK2000L	Model
Codice	TKB#XX10CC22_ / TKB#XX10CC11	TKC#XX20CC22_ TKC#XX20HC22_ / TKC#XX20CF21_ TKC#XX20HF21A	TKC#XX30CC22_ TKC#XX30HC22_/ TKC#XX30CF21_ TKC#XX20HF21A	TKC#XX40CC22_ TKC#XX40HC22_/ TKC#XX40CF21_ TKC#XX40HF21A	TKC#XX41CC22_ TKC#XX41CC21_	Code
Volume refrigerato (lt)*	150	500	1000	2000	1400**	Refrigerated volume (lt)*
Temperatura d'impiego	25°C					Operating temperature
Alimentazione	230V 50Hz / 115V 60Hz					Supply
Potenza frigorifera (in raffreddamento)	245 W * / 250 W*	470 W* / 410 W*	660 W* / 670 W*	870 W* / 830 W*	790 W ** / 770 W**	Cooling capacity (cooling)
Potenza elettrica (raffreddamento)	150 W *	190 W* / 200 W*	240 W* / 260 W*	350 W* / 310 W*	425 W ** / 455 W**	Power consumption (cooling)
Refrigerante ecologico	R290 / R134a	R290	R290	R290	R290	Ecological refrigerant
Temperatura ambiente	+10° / +38 °C					Ambient temperature
Temperatura acqua	+5° / +30 °C				+5° / +15 °C	Water temperature
Dimensioni (mm)	215x 361x 315(h)	310 x 310 x 416 (h)	310 x 310x 458 (h)	310 x 310x 500 (h)	310 x 310x 500 (h)	Dimensions (mm)
Peso (kg)	12,2	16,5	19,7	21,4	25	Weight (kg)

* Reported value refers to the following condition: room temperature 30°C, water temperature 25°C

** Reported value refers to the following condition: room temperature 30°C, water temperature 8°C, considering a well insulated tank

Alla data are approximate and they may change without notice by TECO

I dati in tabella sono indicativi e possono essere cambiati a giudizio TECO