

Modello	TK3000	TK9000	TK5K	TK8K	Model
Codice	TKD#XX50CC22_ TKD#XX50CC21_	TKD#XX63CC22_ TKD#XX63CC22_	TKE#XX70HX52S	TKE#XX80HX57S	Code
Volume refrigerato (lt)	3000	9000	-		Refrigerated volume (lt)
Temperatura d'impiego	25°C (77°F)				Operating temperature
Alimentazione	230V 50Hz or 115V-60Hz	230V 50Hz or 115V-60Hz	220-240V 50Hz 1ph	380-415V 50Hz 3ph	Supply
Potenza frigorifera (in raffreddamento)	2200 W **	3300 W *	5,8 KW *	8,7 KW *	Cooling capacity (cooling)
Potenza elettrica (in raffreddamento)	750 W **	1200 W *	2030 W *	4350 W *	Power consumption (cooling)
Potenza elettrica (in riscaldamento)	800 W **	1200 W *	1500 W **	2800 KW **	Power consumption (heating)
Refrigerante	R290	R290	R410a	R410a	Refrigerant
Temperatura ambiente	+16° / +38 °C (61° F - 100° F)		+5° / +38 °C (41° F - 100° F)		Ambient temperature
Temperatura acqua	+8° / +30 °C (47° F - 86° F)		+5° / +35 °C (41° F - 95° F)		Water temperature
Dimensioni (mm)	395x600x565(h)		816x690x835(h)	816x690x850 (h)	Dimensions (mm)
Peso (kg)	37	47	79	105	Weight (kg)
* Reported value refers to the following condition: room temperature 30°C, water temperature 25°C					
** Reported value refers to the following condition: room temperature 5°C, water temperature 25°C					